

HİDROLİK ELEKTRİK POMPASI SEÇİM TABLOSU

HYDRAULIC ELECTRIC PUMP SELECTION CHART

MODEL	Tek Kademe Single Stage	Akış / Flow (in ³)	Kapasite / Capacity (ton)													
			5	10	15	25	30	50	75	100	150	200	250	300	400	500
			1" Kaldırmak için gerekli zaman (sn) / Required time (seconds) for cylinder to lift 1 inch													
EPB-3B+	1.kademe / 1st.stage	4.00	0.3	0.6	0.8	1.3	1.7	2.8	4.0	5.1						
	2.kademe / 2st.stage	0.27	4.1	8.4	12.2	19.3	25.5	41.2	60.3	76.8						
EPB-6B+	1.kademe / 1st.stage	10.17	0.1	0.2	0.3	0.5	0.7	1.1	1.6	2.0	3.0	4.1				
	2.kademe / 2st.stage	0.65	1.7	3.5	5.0	7.9	10.5	16.9	24.8	31.5	47.5	63.4				
EPB-10B+	1.kademe / 1st.stage	10.17	0.1	0.2	0.3	0.5	0.7	1.1	1.6	2.0	3.0	4.1	5.5			
	2.kademe / 2st.stage	1.00	1.1	2.3	3.3	5.2	6.8	11.0	16.1	20.5	30.9	41.2	56.2			
EPB-20B+	1.kademe / 1st.stage	10.17	0.1	0.2	0.3	0.5	0.7	1.1	1.6	2.0	3.0	4.1	5.5	7.0	8.7	11.1
	2.kademe / 2st.stage	1.67	0.7	1.3	2.0	3.1	4.1	6.6	9.6	12.3	18.5	24.7	33.7	42.3	53.1	67.8

 Tavsye edilen uygulama /
Recommended application

 Seçici kullanım /
Selective use

 Tavsye edilmez /
Not recommended