

AÇILI MAKASLI PLATFORM / LIFT & TILT TABLE**NL-TTA 15****NL-TTA 40****NL-TTA 80**

	NL-TTA 15	NL-TTA 40	NL-TTA 80	
Kaldırma kapasitesi / Capacity	150	400	800	kg
Tabla ölçüleri UxG / Table size TxW (l x b)	830 x 500	830 x 520	830 x 520	mm
M ölçüsü / Dimensions M	830	830	930	mm
N ölçüsü / Dimensions N	748	830	830	mm
H1 Tabla yüksekliği / Table height H1 (min/max)	415/ 880	435/ 900	440/ 1000	mm
H2 Tabla yüksekliği / Table height H1 (min/max)	415/ 1400	435/ 1560	438/ 1570	mm
H3 Kol yüksekliği / Handle height H3 (min/max)	1100	1130	1130	mm
Teker çapı / Wheel diameter	125	150	150	mm
Toplam ölçüler / Overall Size	500 x 1010	520 x 1355	520 x 1355	mm
Maks. yüks. için pompalama / Foot pedal to max. height	20	55	80	
Net ağırlık / Net weight	92	123	145	kg

Art.No. 51500039

NL-TTA 15

Art.No. 51500040

NL-TTA 40

Art.No. 51500041

NL-TTA 80

- **NETLIFT'in bu yeni ürünü paletlerden ve kutulardan kolayca yük boşaltmayı veya yüklemeyi sağlar.**
- **Tabla maksimum yükseklikte ve yatıkken tabla üzerindeki kutu veya paletlerden en alttaki ürünleri dahi rahatlıkla indirmek mümkündür.**
- **Platform, ayak pompası ile yükseltilmektedir. Tabla maksimum yüksekliğe ulaştıkça 45° lik bir açı ile öne doğru yatar. Dahili sabitleme kulakçıkları sayesinde yükünüz sabit kalır.**

- The Lift&Tilt Tables from NETLIFT are specifically designed to allow an operator to feed and unload parts from the boxes or containers quickly and easily without lifting, bending, stretching or reaching.
- When in its lift and tilt position, the unit holds boxes or containers at a comfortable working height and angle that allows operators to easily reach parts even at the bottom of the container.
- The working table is elevated by means of a foot actuated hydraulic cylinder. As the table is raised, it automatically tilts to an angle of 45 at full elevation. Built-in retaining lip keeps containers in place.

